



A-15 HD EFP SPECIFICATIONS

THE CHASSIS

Ford LCF-(Low Cab Forward) series 19,000 lb. [8165 kg] GVWR
 Ford Power Stroke 4.5 liter 200 hp V-6 cylinder EFI Diesel engine
 7000lb Front Axle 13,500 Rear Axle, Stabilizer Bars Front & Rear
 19.5 Wheels
 50,000 PSI Heavy Duty Frame
 5 Speed TorqShift Automatic Transmission with PTO
 Heavy duty cooling system including engine oil cooler
 1 - 40 Gallon (182 Liter) Fuel Tank
 Power Assisted Steering
 Power Assisted Brakes 4 Wheel ABS
 Tilt-Telescoping Steering Wheel
 Heavy Duty Shock Absorbers
 Dual Maintenance Free Batteries 1800 CCA
 Gauge Package-Voltmeter, Oil Pressure Temperature and Fuel Indicators
 Front Cab Air Conditioning
 AM/FM Stereo Radio with Clock
 Underbody Undercoating (Petroleum Based)
 Tinted glass
 2 side view stainless steel mirrors

SAFETY EQUIPMENT

ICC First Aid Kit
 Fire Extinguisher
 CO Detector
 Remote Backup Alarm
 Tow Hooks

AVAILABLE OPTIONS

DC Operated Stabilizing Jacks
 Color or BW Back-up Camera
 Logo from Customer Supplied Art work
 Custom Exterior Colors
 Multi Line Telephone system
 Curb Side Awning
 Burglar alarm pager

THE HOUSING

Parameter Riveted Smooth .090 Aluminum Skin
 Reinforced Interior Walls, Floor and Ceiling
 Sonex or Equal Sound Reducing Ceiling Treatment
 Industrial Grade Tight Looped Anti-Static Carpet
 Nonflammable, Hard Packed Insulation
 Custom Built Equipment Racks with Operator Console
 Custom Heavy Duty .125 Aluminum Tread Plate Roof with Rear Access Ladder
 Exterior Paint is Multi-Coat Imron or Equal Catalytic paint (White)
 30,000 BTU Commercial Air Conditioner with Shook Hot Gas Bypass Valve Modification and Air Plenum.
 5KW Electric Heat Strip in AC Unit
 UL® Approved Power Panel with Separate Circuit Breakers and Individual Power Strips in each rack
 12.0 KW PTO Driven 60Hz Generator with Remote Start/Stop and Manual Changeover Switch
 13.2 KVA Isolation Transformer for Shore Power with Taps for 195/208/220/230 VAC
 Digital Voltage/Current/Frequency Metering
 (1) AC Duplex Maintenance Outlet located on the Curb Side
 25 Feet (7.6m) #6-3 with Ground Type "SO" Cable with Inlet Connector
 30 Amp DC Converters with 40 Amp Battery Charger
 Custom Engraved External I/O Video/Audio Panel with Light
 Interior 12 V DC Ceiling Lights
 5 - Removable Swivel Task Chair (s) with Tie Down. (See plan for quantity and location)
 Remote Controlled Burglar Alarm System on All Access Doors
 Custom Sized Aluminum Bally Boxes with Ice Breaker Handles
 Dark Gray Rubber Tile flooring
 Two-Tone Interior Carpeting with Chair Rail
 Custom Stow Away Steps on curb side
 On board Alarm System

Web: www.shook-usa.com - E-mail: shook@shook-usa.com - Toll Free: 1-888-651-5775

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE